










900 Plinski roštilji

Model							
	mm	Kg	m ³	kW	kcal/h	Btu/h	kW
 <p>K9GFL05TTRP</p>	a 900	66	0,27	8	6878,8	27300	-
	b 450						
h 250							
Glatka ploča, niskouglični čelik, gornja jedinica							
 <p>K9GFR05TTRP</p>	a 900	67	0,27	8	6878,8	27300	-
	b 450						
h 250							
Rebrasta ploča, niskouglični čelik, gornja jedinica							
 <p>K9GFL05VVRP</p>	a 900	80	0,60	8	6878,8	27300	-
	b 450						
h 850							
Glatka ploča niskouglični čelik + otvoreni ormarić							
Izborno K9PORTA Vrata							
 <p>K9GFR05VVRP</p>	a 900	80	0,60	8	6878,8	27300	-
	b 450						
h 850							
Rebrasta ploča, niskouglični čelik + otvoreni ormarić							
Izborno K9PORTA Vrata							

900 Plinski roštilji

Model							
	mm	Kg	m ³	kW	kcal/h	Btu/h	kW
 <p>K9GFL10TTRP</p>	a 900	110	0,50	13,8	11866	47090	-
	b 900						
h 250							
Glatka ploča, niskouglični čelik, gornja jedinica							
 <p>K9GFR10TTRP</p>	a 900	110	0,50	13,8	11866	47090	-
	b 900						
h 250							
½ glatka ½ rebrasta ploča, niskouglični čelik							
 <p>K9GFL10VVRP</p>	a 900	135	1,08	13,8	11866	47090	-
	b 900						
h 850							
Glatka ploča, niskouglični čelik + otvoreni ormarić							
Izborno K9PORTA Vrata							
 <p>K9GFR10VVRP</p>	a 900	135	1,08	13,8	11866	47090	-
	b 900						
h 850							
½ glatka ½ rebrasta ploča, niskouglični čelik + otvoreni ormarić							
Izborno K9PORTA Vrata							